


## UM 45-FLKS34

Order No.: 2962670



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2962670>

VARIOFACE module, with screw connection and flat-ribbon cable connector, for assembly on NS 35/7.5, 34 positions

### Commercial data

|                          |                    |
|--------------------------|--------------------|
| EAN                      | 4017918087340      |
| Pack                     | 1 pcs.             |
| Customs tariff           | 85369010           |
| Weight/Piece             | 0.12 KG            |
| Catalog page information | Page 245 (IF-2007) |

### Product notes

WEEE/RoHS-compliant since:  
03/30/2007



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

### Technical data

#### General data

|   |           |
|---|-----------|
| Nominal voltage $U_N$                     | < 50 V AC |
|   | 60 V DC   |
| Max. current carrying capacity per branch | 1 A       |
| Number of positions                       | 34        |
| Width                                     | 85 mm     |

|   |                  |
|---|------------------|
| Height                                  | 53 mm            |
| Depth                                   | 45 mm            |
| Ambient temperature (operation)         | -20 °C ... 50 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |
| Test voltage input/output               | 500 V AC         |
| Mounting position                       | Any              |
| Standards/regulations                   | IEC 60664        |
|   | DIN VDE 0110     |
| Pollution degree                        | 2                |
| Surge voltage category                  | II               |

#### Connection data

|  |                              |
|--|------------------------------|
| Connection 1                           | PCB connection               |
| Connection in acc. with standard       | IEC / EN                     |
| Type of connection                     | Screw connection             |
| Conductor cross section solid min.     | 0.14 mm <sup>2</sup>         |
| Conductor cross section solid max.     | 1.5 mm <sup>2</sup>          |
| Conductor cross section stranded min.  | 0.14 mm <sup>2</sup>         |
| Conductor cross section stranded max.  | 1.5 mm <sup>2</sup>          |
| Conductor cross section AWG/kcmil min. | 26                           |
| Conductor cross section AWG/kcmil max  | 16                           |
| Stripping length                       | 6 mm                         |
| Screw thread                           | M3                           |
| Connection 2                           | Flat-ribbon cable connection |
| Type of connection                     | Pluggable                    |

#### Certificates / Approvals



Certification CUL, GOST, UL

#### CUL

|                       |       |
|-----------------------|-------|
| Nominal voltage $U_N$ | 125 V |
| Nominal current $I_N$ | 1 A   |

**UL**


|                       |       |
|-----------------------|-------|
| Nominal voltage $U_N$ | 125 V |
| Nominal current $I_N$ | 1 A   |

**Accessories**

| Item                   | Designation              | Description   |
|------------------------|--------------------------|---|
| <b>Cable/conductor</b> |                          |   |
| 2299479                | FLK 34/EZ-DR/ 50/KONFEK  | Round cable set, with two 34-pos. socket strips (1:1 connection), cable length: 0.5 m |
| 2299482                | FLK 34/EZ-DR/ 100/KONFEK | Round cable set, with two 34-pos. socket strips (1:1 connection), cable length: 1 m   |
| 2299495                | FLK 34/EZ-DR/ 150/KONFEK | Round cable set, with two 34-pos. socket strips (1:1 connection), cable length: 1.5 m |
| 2299505                | FLK 34/EZ-DR/ 200/KONFEK | Round cable set, with two 34-pos. socket strips (1:1 connection), cable length: 2 m   |
| 2299518                | FLK 34/EZ-DR/ 300/KONFEK | Round cable set, with two 34-pos. socket strips (1:1 connection), cable length: 3 m   |
| 2299521                | FLK 34/EZ-DR/ 400/KONFEK | Round cable set, with two 34-pos. socket strips (1:1 connection), cable length: 4 m   |
| 2299534                | FLK 34/EZ-DR/ 600/KONFEK | Round cable set, with two 34-pos. socket strips (1:1 connection), cable length: 6 m   |
| 2299547                | FLK 34/EZ-DR/ 800/KONFEK | Round cable set, with two 34-pos. socket strips (1:1 connection), cable length: 8 m   |
| 2299550                | FLK 34/EZ-DR/1000/KONFEK | Round cable set, with two 34-pos. socket strips (1:1 connection), cable length: 10 m  |
| 2295059                | FLK EZ-DR.../.../...     | Round cable, with preassembly, not shielded, variable cable length                    |

**Diagrams/Drawings**

Circuit diagram



**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact  
Technical modifications reserved;