



**PART AFTER
UNRESTRICTED RECOVERY**

REVISIONS			
LTR	DESCRIPTION	DATE	APPROVED
A	"U" TOL. WAS $\pm 10\%$	8-7-84	JLJ

TABLE OF DIMENSIONS:

PART NUMBER	H		J			P	R	S	T	JO	HW	JW	U
	Min	Max	POLY Min	VITON Min	Max								
	a	b	a	a	b								
202D211-X-32	.88 (22,3)	.45 (11,5)	.88 (22,3)	.55 (13,9)	.25 (6,4)	3.00 (76,2)	.46 (11,7)	.12 (3,05)	.040 (1,02)	2.23 (56,6)	.06 (1,52)	.045 (1,14)	.55 (14,0)
202D221-X-32	1.01 (25,6)	.59 (15,0)	1.01 (25,6)	.63 (16,0)	.29 (7,4)	3.25 (82,6)	.48 (12,2)	.12 (3,05)	.040 (1,02)	2.36 (59,9)	.06 (1,52)	.045 (1,14)	.59 (15,0)
202D232-X-32	1.16 (29,4)	.74 (18,8)	1.16 (29,4)	.72 (18,2)	.33 (8,4)	3.50 (88,9)	.48 (12,2)	.12 (3,05)	.040 (1,02)	2.48 (63,0)	.07 (1,78)	.045 (1,14)	.60 (15,2)
202D242-X-32	1.34 (34,0)	.90 (22,9)	1.34 (34,0)	.84 (21,3)	.38 (9,7)	4.00 (101,6)	.48 (12,2)	.12 (3,05)	.040 (1,02)	2.87 (72,9)	.07 (1,78)	.045 (1,14)	.62 (15,7)
202D253-X-32	1.47 (37,3)	1.16 (29,5)	1.47 (37,3)	.91 (23,1)	.41 (10,5)	4.25 (108,0)	.55 (14,0)	.12 (3,05)	.065 (1,65)	2.85 (72,4)	.08 (2,03)	.045 (1,14)	.70 (17,8)
202D263-X-32	1.72 (43,6)	1.34 (34,1)	1.72 (43,6)	1.07 (27,1)	.48 (12,2)	4.50 (114,3)	.60 (15,2)	.12 (3,05)	.065 (1,65)	2.92 (74,2)	.08 (2,03)	.045 (1,14)	.78 (19,8)
202D274-X-32	1.97 (50,0)	1.62 (41,2)	1.97 (50,0)	1.24 (31,4)	.56 (14,3)	4.65 (118,1)	.60 (15,2)	.12 (3,05)	.065 (1,65)	2.86 (72,6)	.09 (2,29)	.055 (1,40)	.78 (19,8)
202D285-X-32	2.47 (62,7)	1.85 (47,0)	2.47 (62,7)	1.54 (39,1)	.69 (17,6)	4.75 (120,7)	.63 (16,0)	.12 (3,05)	.08 (2,03)	2.78 (70,6)	.10 (2,54)	.055 (1,40)	.81 (21,0)
202D296-X-32	2.73 (69,3)	2.35 (59,7)	2.73 (69,3)	1.70 (43,1)	.77 (19,6)	5.00 (127,0)	.63 (16,0)	.12 (3,05)	.08 (2,03)	2.64 (67,1)	.10 (2,54)	.055 (1,40)	.81 (21,0)
202D299-X-32	3.22 (81,7)	2.64 (67,1)	3.22 (81,7)	2.01 (51,0)	.90 (22,9)	5.25 (133,4)	.63 (16,0)	.12 (3,05)	.08 (2,03)	2.70 (68,6)	.10 (2,54)	.055 (1,40)	.81 (21,0)

NOTES:

1. All dimensions are in inches (millimeters)
2. Dimensions appearing in Table are as follows:
a - As supplied
b - After unrestricted recovery
3. Part shall have injection and vent ports, located as shown.

ORDERING INFORMATION:

Base part number 202D221 -4 -32
 Material dash number _____
 -3 Polyolefin, semi-rigid (RT-301/7)
 -4 Polyolefin, flexible (RT-1304)
 -12 Viton (RT-1312)
 -25 Elastomer, fluid-resistant (RT-1325)
 Modification number _____

SPECIFICATION CONTROL DRAWING (LIMITED DISTRIBUTION)

If this document is printed it becomes uncontrolled.
Check for the latest revision.

THIS DRAWING AND THE INFORMATION SET FORTH HEREON ARE THE PROPERTY OF RAYCHEM CORPORATION, AND ARE TO BE HELD IN TRUST AND CONFIDENCE. PUBLICATION, DUPLICATION, DISCLOSURE, OR USE FOR ANY PURPOSE NOT EXPRESSLY AUTHORIZED IN WRITING BY RAYCHEM CORPORATION IS PROHIBITED.	DRAWN	<i>R. Watson 10-8-80</i>	Raychem	RAYCHEM CORPORATION 300 CONSTITUTION DRIVE MENLO PARK, CALIFORNIA 94025		
	CHECKED	<i>Phyllis 10/14/80</i>		TITLE	BOOT, STRAIGHT, WITH LIP	
	DESN APPD	<i>Phyllis 10/14/80</i>	MFG APPD	CODE IDENT.	NO. 00080	DWG. NO. 202D2XX-X-32
	QC APPD	<i>Long 10/19/80</i>	MKTG APPD	NO. 00080	SHEET 1 OF 1	
	Trace Service	<i>R. Watson 10/19/80</i>	PROJECT	SIZE 8	SCALE	