



- 1) JACKET COLOR: BLACK
- 2).E-GREEN; L-BLACK ; N-WHITE

- TESTING:
- 1) 100% OPEN & SHORT TESTING
  - 2) INSULATION RESISTANCE: 100M ohm(min)
  - 3) VOLTAGE: DC500V/1min
  - 4) ROHS COMPLIANT

E243929 (UL) SJT 3×16AWG(1.31mm<sup>2</sup>) VF-1 SHIELDED 60°C 300V CSA 228191 SJ  
 T 3×16AWG(1.31mm<sup>2</sup>) FT2 SHIELDED 60°C 300V -LF-

NO.	SPECIFICATION	COLOUR	MATERIAL	AMOUNT
①	Load terminals 98661	Silver	Cu	2P
②	Grounding terminal 97475	Silver	Cu	1P
③	Model aircraft 8661AN-3P	WHITE	PBT	1PCS
④	Plug JLL-301	BLACK	PVC Cu	1PCS
⑤	Wire SJT 16AWG/3C 60°	BLACK	PVC Cu	1PCS
⑥	Ties	BLACK		1PCS



Scale	1:1						Name	Item No. <b>A-PC2314-030030-1</b>
TOLERANCE					Drawn	3/26/12	Miller	
X.X	±0.40				Approved	3/26/12	Warner	Title 5-15P to Open, 3M, SJT#16*3C 60C SHIELDED
X.XX	±0.25							Drawing No.
X.XXX	±0.15							rev00
Angle	±3°							
								Replace
								Sheet

